



Packaging

1 gallon (3.80L) bottles
5 gallon (18.92L) pails

Storage

1. Store pails in a cool, dry location.
2. Store at a temperature between 40°F (4°C) and 90°F (32°C).
3. Store out of direct sunlight.
4. Protect pails from weather and other damage.

Shelf Life

2 Years

Color

White liquid; dries clear

Product Description

Admix 2000 is a 100% acrylic polymer admixture for cementitious products. Admix 2000 is used to increase tensile, bond, and flexural strength of approved products.

Features	Benefits
VOC Compliant	Low Odor and toxicity
Cost effective	Saves money compared to sand-blasting
Non-Emulsifying	Once dried becomes a constant chemical lock and becomes water resistant when dry
Chemical and UV Resistant	Long-term performance
Easy to Use	Mix with the water to be used

Basic Uses

Admix 2000 is used as an admixture to improve performance of approved products.

Area of Use

Admix 2000 may be added to the following products:

1. Cementitious stucco
2. Approved cement-based products
3. Liquid component in a sand/cement slurry coat
4. Scratch and brown coats
5. Scrub coat

Surface Preparation

Mix Admix 2000 thoroughly prior to use. Add the specified amount of Admix 2000 to the water in the mixer. The amount of water used is per the product's data sheet, but should be reduced by the quantity of Admix 2000 used. Add the product dry mix to Admix 2000 and water solution according to product's application instructions. Mix slowly until achieving an even consistency. Do not over mix. As a general use admixture to improve adhesion, cohesion, tensile, compressive and flexural strengths of portland cement-based materials, the normal ratio of Admix 2000 to clean potable water is one part Admix 2000 to 3 parts water (1:3). Where increased physical and chemical resistance requirements are required follow the table below.

Application	Product	Dilution (water/admix)
One coat Stucco Systems	Superior Uniwall	1:1
Scratch Coat	Superior Premium Cement	1:1
Brown Coat	Superior Premium Cement	1:1
Stucco Finish	Superior Exterior Stucco	3:1
Patch & Repair	Superior SuperSet	1:1
Scrub Coat		Straight Admix 2000

Application

Add product dry mix to diluted Admix 2000 solution according to product's application instructions.

NOTE: Admix 2000 may reduce set time

Curing

Allow the cementitious product to air cure. Protect the wet product when unusual weather conditions are present.

Limitations

DO NOT use Admix 2000 when the ambient and/or surface temperatures are below 40°F (4°C).

DO NOT add any other materials to the mixture of the product without written approval from Superior Stucco

DO NOT deviate in the mixing or application procedures contained in this, or any other Superior Stucco Data Sheets, without the written approval from Superior Stucco

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Cleaning

Cleaning may be accomplished with water immediately after use.

Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

www.StuccoSupplyCo.com

Disclaimer

Stucco Supply (Manufacturer) MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products

are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Stucco Supply's reasonable charges, including travel and labor associated with investigation of such claim.

Technical Assistance

Technical assistance and information is available by calling (408) 292-0454

Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.