



## Coverage

### Standard Mesh:

4.5oz, 475ft<sup>2</sup> (44.1m<sup>2</sup>),  
38"x150' roll

### Starter Mesh:

4.5oz, 118ft<sup>2</sup> (11.0m<sup>2</sup>),  
9.5"x150' roll

## Storage

1. Protect bags from weather and other damage
2. Store bags in a cool, dry location
3. Store out of direct sunlight
4. Store away from direct contact with the ground and/or concrete

## Color

White (with a green stripe)

## Product Description

Superior Stucco Crack-Guard Mesh is an alkali resistant, woven glass fiber fabrics specially designed to be used with Superior Stucco base coats. Meshes are available in a range of weights that provide different levels of strength and impact resistance.

**NOTE:** DO NOT use CG-Mesh in EIF Systems. Use only EIF Reinforcing Mesh in EIF Systems.

Features	Benefits
<i>Alkali Resistant</i>	Able to resist the alkalinity of the base coats
<i>Durable</i>	Durable Long-lasting impact strength

## Basic Uses

Superior Stucco CG-Mesh is designed to reduce surface cracking as part of the Superior Stucco Crack-Guard System, for adding impact resistance over architectural foam shapes, or for adding strength when used with approved Superior Stucco base coats.

The following Superior Stucco Meshes are available:

**CG-Mesh Standard Roll (4.5oz / 38-inch roll):** Superior Stucco CG (Crack-Guard) mesh is designed for use in the Superior Stucco Crack-Guard System and architectural foam shapes.

**CG-Mesh Starter Roll (4.5oz / 9.5-inch roll):** For back wrapping and detail work.

## Area of Use

CG-Mesh may be embedded in the following products:

1. Superior Stucco Crack Guard System
2. All Superior Stucco base coats
3. Architectural foam

## Surface Preparation

All surfaces to receive application must be properly cured, clean and free of debris, dirt, dust, efflorescence, grease, oils, curing agents, and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. It may be necessary just prior to application to dampen all surfaces that are to receive the Crack-Guard Base with clean, potable water.

## Application

1. Apply a coat of the desired Superior Stucco base coat according to the appropriate Product Data Sheet's application procedures.
2. Embed the Reinforcing Mesh into the wet base coat using a steel trowel, troweling from the center of the mesh to the edges. Avoid Wrinkles in the mesh.
3. Ensure that no Reinforcing Mesh is visible. Add base coat where needed.

## Limitations

**DO NOT** deviate from the application procedures contained in this, or any other Superior Stucco Product Data Sheets, without written approval from San Jose Stucco Supply.

**DO NOT** allow any mesh to come in contact with petroleum products of any kind.

**DO NOT** allow mesh to show through base coat. Correct as necessary.

**NOTE:** Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

## Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

**KEEP OUT OF REACH OF CHILDREN**

[www.StuccoSupplyCo.com](http://www.StuccoSupplyCo.com)

### Disclaimer

Stucco Supply (Manufacturer) MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products

are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

### Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Stucco Supply's reasonable charges, including travel and labor associated with investigation of such claim.

### Technical Assistance

Technical assistance and information is available by calling (408) 292-0454

### Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.