



Product Description

Superior Fog Coat is a spray-applied cement-based, water-soluble, pigmented coating, which cures to become an integral part of the stucco surface and maintains original finish characteristics. It is an economical method to achieve color uniformity and to enhance older existing painted stucco.

Basic Uses

Superior Fog Coat is designed for maintaining the appearance and color of stucco. It can be used to refresh, change color, or blend repairs of existing stucco. Superior Fog Coat can also be used to correct color variations in new stucco that are typically caused by jobsite conditions.

Area of Use

Superior Fog Coat may be applied over the following product:

1. Superior Exterior Stucco

Features & Benefits

- Integral Color
- Lasting, uniform color that resists fading or discoloration
- UV resistant
- Durable
- Long life-cycle with minimal maintenance
- Fire Resistant
- Economical product and easy to apply

Optional Product Upgrades/Enhancements

Product	Benefit
Admix 2000, Ultra-Tite 60, Acrylic Bonder	Liquid admixtures that reduce cracking and increase tensile, bond, and flexural strengths.

Coverage

Range from approximately 400ft² to 900ft² (37.2m² to 83.6m²). Coverage may vary due to ambient temperature, surface temperature, surface porosity, mixing methods, and/or application methods.

Packaging

Multi-layered, moisture resistant, 25 lb. bags.

Storage

1. Protect bags from weather and other damage
2. Store bags in a cool, dry location
3. Store out of direct sunlight
4. Store away from direct contact with the ground and/or concrete

Shelf Life

1 Year

Color

Natural Grey

FOG COAT

Surface Preparation

All surfaces to receive application must be clean and free of debris, dirt, dust, efflorescence, grease, oils, curing agents and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Just prior to application, dampen all surfaces that are to receive Fog Coat with clean, potable water.

Mixing

1. Fog Coat is mixed at a ratio of two parts Fog Coat powder to five parts clean, potable water (by volume). Always add powder to water.
2. Start with enough water to make a paste.
3. Stir contents of pail for a minimum of 3 minutes.
4. Wait 5 minutes for material to take an initial set.
5. Retemper adding the rest of the water to reach desired consistency.
6. Pour contents through a paint screen into another clean, 5 gallon pail.
7. Optional: Add Superior Admix 2000.
8. Pour contents through another paint screen into sprayer tank.

NOTE: May need to sift through paint strainer 3 to 4 times. Apply Fog Coat to a test area to verify the color match prior to a full application.

Application

Fog Coat may be applied using a spray method.

1. Using a Hudson-type sprayer, spray all surfaces using a circular motion, begin application at a corner and end at a corner.
2. Avoid saturation.
3. Repeat as needed

NOTE: Multiple light even coats will produce better results than one heavy coat. Avoid puddling or running. Protect applied product from inclement weather conditions until cured.

Curing

Curing and/or drying time may vary due to climatic conditions. Drying should occur within 24 hours at an ambient and surface temperature of 70°F (21°C) and 55% R.H. When hot, dry, or windy conditions exist, light moist curing and/or protection should be provided. All freshly applied material must be protected from inclement weather until material has sufficient strength not to be damaged. Full curing strength typically occurs in approximately 28 days.

Limitations

DO NOT apply product when the ambient and surface temperature is below 40°F (4°C).* The ambient and surface temperature must maintain the above requirements until material has sufficient strength not to be damaged (See CURING). Material that is allowed to freeze may suffer irreparable damage.

DO NOT add any other materials to the mixture of the product without written approval from Stucco Supply.

DO NOT deviate in the mixing or application procedures contained in this, or any other Product Data Sheets, without written approval from Stucco Supply.

DO NOT spot fog. Fogged areas may age differently over time.

DO NOT apply Fog Coat if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

DO NOT add any more water than prescribed.

DO NOT saturate the wall during preparation and/or water curing.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Due to job conditions beyond the control of Superior Stucco Products, we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.

Cleaning

Cleaning may be accomplished with water immediately after use.

Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

www.StuccoSupplyCo.com

Disclaimer
Stucco Supply (Manufacturer) MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products

are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

Claims
Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Stucco Supply's reasonable charges, including travel and labor associated with investigation of such claim.

Technical Assistance
Technical assistance and information is available by calling (408) 292-0454

Warranty
The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.