



Coverage

Approximately 10 to 12 sq-yds
per 50lb bag

Packaging

Multi-layered, moisture resistant,
50 lb. bags.

Storage

1. Protect bags from weather and other damage
2. Store bags in a cool, dry location
3. Store out of direct sunlight
4. Store away from direct contact with the ground and/or concrete

Shelf Life

1 Year

Color

Natural Grey

Custom colors are also available.

Product Description

Superior Shower Finish is a mechanically-blended compound of portland cement, hydrated lime, inert aggregates, and specific additives, designed to achieve a steel trowel finish over a portland cement base. It requires the addition of only clean water for mixing. Superior Shower Finish will provide excellent bond to any properly prepared portland cement base surface. If you prefer to color Superior Shower Finish, it will achieve its own variance of color. It may be used on interior or exterior surfaces to provide a highly condensed, smooth surface. May use sealer or to be painted.

Basic Uses

Provides a hardy, enduring finish over a Portland cement base coat. If using over cement board the joints need to be addressed first then a crack guard base coat is recommended with alkali-resistant mesh embedded in the base coat over the entire surface.

Area of Use

1. Showers
2. Bathrooms
3. Swimming Pool Dressing Rooms
4. Locker Rooms
5. Laundry Rooms

Features & Benefits

- Color integrated
- Lasting durability, protects as it decorates.
- Mixes easily with potable water.
- Genuine lath and portland cement plaster finish.
- Low maintenance, economical.
- Weather resistant - does not deteriorate with age.
- Adds aesthetic value to any building.
- Impervious to termites.

Optional Product Upgrades/Enhancements

Product	Benefit
Admix 2000, Ultra-Tite 60, Acrylic Bonder	Liquid admixtures that reduce cracking and increase tensile, bond, and flexural strengths.
Crack Guard Base Coat	To reduce and mitigate cracking.

Surface Preparation

New portland cement substrates should be properly cured prior to application of Superior Shower Finish (approximately 7 days). All receiving surfaces must be structurally sound, clean, free of dust, dirt, silicones, paint products, efflorescence or any other contaminant which could impair the natural bond. Surface defects, such as cracks, holes or voids should be repaired prior to application. Basecoat should be plum, level, and square to prevent uneven thickness of Superior Shower Finish.

Mixing

Superior Shower Finish should be mechanically mixed for approximately 15 minutes to provide maximum workability.

For **Hand Application**: 3 to 5 qts. of clean water per 50 lb. bag will be necessary. Add approximately 1/2 of the required water to the mixer. With the blades running, carefully add the Superior Shower Finish. Allow ample time for initial mixing, add remaining mix water, and complete mixing to produce a smooth, workable consistency. Disengage mixing and let the material take on its' initial "set" (3 to 5 minutes), then adjust water to desired consistency and only mix long enough to achieve desired material.

For **Machine or Spray Application**: Additional mixing water may be necessary.

NOTE: For maximum strength and increased moisture resistance, add Superior Acrylic Bonder to the mix water using a 3:1 ratio (3 parts water/1 part Acrylic Bonder).

Application

Apply Superior Shower Finish to a thoroughly dry basecoat which has been evenly wet by using the SSD method (to control suction). Allow surface moisture to dissipate prior to application. Avoid the use of excessive moisture during application. Superior Shower Finish should be applied to an approximate thickness of 1/8 inch (3mm). Trowel apply the initial coat (scratch coat) evenly to the substrate with enough pressure to ensure tight contact. After the basecoat has been covered completely, double back and fill out to a true, even surface. Allow material to dehydrate (begin to lose its moisture to the basecoat and to the ambient air) and then trowel it well, firmly compacting the material with water, free from catfaces and/or other blemishes or irregularities. Avoid unnecessary "build-ups" which cause shrinkage or check-cracking. A properly prepared basecoat will prevent leveling with the Superior Shower Finish. Recommended to complete both the scratch coat and the finish coat in the same day.

Limitations

DO NOT apply product when the ambient and surface temperature is below 40°F (4°C). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system until fully dry. It is the sole responsibility of the applicator to determine when this product is fully dry.

DO NOT apply Superior Stucco Shower Finish if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and or oils.

DO NOT add any more water than is prescribed when diluting the product.

DO NOT add any other materials to the mixture of the product without written consent of Superior Stucco

DO NOT deviate in the mixing or application procedures contained in this or related Product Information Sheet(s).

DO NOT use a Jiffiler type mixer that exceeds 500RPM

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Due to job conditions beyond the control of Superior Stucco we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.

Cleaning

Cleaning may be accomplished with water immediately after use.

Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

www.StuccoSupplyCo.com

Disclaimer
Stucco Supply (Manufacturer) MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products

are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

Claims
Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Stucco Supply's reasonable charges, including travel and labor associated with investigation of such claim.

Technical Assistance
Technical assistance and information is available by calling (408) 292-0454

Warranty
The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.