

# ***SUPERIOR STUCCO ACRYLIC FINISH***

## **DESCRIPTION:**

**SUPERIOR STUCCO ACRYLIC FINISH** is manufactured with a pure acrylic emulsion binder with the highest-grade aggregates. Special proprietary additive produces an outstanding flexible finish. It is a Non Toxic, Antimicrobial Finish with High Dirt Pick-up Resistance (**High DPR**).

## **BASIC USES:**

**SUPERIOR STUCCO ACRYLIC FINISH** is designed for interior and exterior finish coating with freestyle texture over a number of substrates. **SUPERIOR STUCCO ACRYLIC FINISH** can be applied by hand or by sprayer.

## **APPLICATION:**

Take care that all surfaces to be covered are free of loose debris, dirt, oil, efflorescence, curing agent, cleaning solutions and foreign matter. Ensure that all surfaces are smooth and free of any irregularities. Pressure washing, mechanical sanding, scrapping, chipping or sandblasting may accomplish smoothing and cleaning the surface. Glossy or smooth surfaces must be roughened to ensure a proper bond. It's very important to ensure the surface has been properly prepared. **DO NOT** apply **SUPERIOR STUCCO ACRYLIC FINISH** until surface is free of all contaminants.

✓ Apply **SUPERIOR STUCCO ACRYLIC PRIMER**, (may be rolled or sprayed).

✓ Apply a uniform coat of **SUPERIOR STUCCO ACRYLIC FINISH**, no thicker than the largest aggregate, to the substrate

✓ Immediately following the applicator, use a plastic float or stainless steel trowel in a consistent motion to obtain the desired finish.

\*Tilt up or poured in place concrete using bond breaking agents, needs to be approved by **Stucco Supply**.

## **MIXING:**

1. See color bottle for mixing instructions.
2. **Stucco Supply's SUPERIOR STUCCO ACRYLIC FINISH** must be thoroughly mixed immediately prior to use.
3. If multiple pails are being used, intermix pails to achieve consistency.

## **COLOR:**

**Stucco Supply's SUPERIOR STUCCO ACRYLIC FINISH** is white and may be colored using **Superior Stucco Color Tinting System**.

**Stucco Supply** offers 30 different standard colors on request.

## **AREA OF USE:**

**SUPERIOR STUCCO ACRYLIC FINISH** may be applied to:

1. Brown Coat
2. Stucco
3. One-Coat
4. Masonry
5. Poured-in-place and/or tilt-up concrete

## **CURING:**

**SUPERIOR STUCCO ACRYLIC FINISH** should be fully cured in no less than 24 hours. Curing time will vary due to surface temperature, porosity, ambient temperature and/or application method.

## **NOTE:**

Protect applied product from inclement weather until fully dried. **DO NOT APPLY SUPERIOR STUCCO ACRYLIC FINISH** when the temperature is below 40-Degrees F. or above 100-Degrees F. This range of temperature must be kept for 48 hours to ensure proper curing.

## **STORAGE:**

**SUPERIOR STUCCO ACRYLIC FINISH** should be stored in a cool, dry place out of direct sunlight and other possible damage. Keep **SUPERIOR STUCCO ACRYLIC FINISH** above 40-Degrees F. and below 100-Degrees F.

**CLEAN-UP:** Clean up can be done with water immediately after use.

## **GUARANTEE:**

No Warranty of Merchantability of Fitness for a particular purpose with respect to the product sold herein except that the quality of the ingredients shall be in accordance with **Stucco Supply** specifications. It is agreed and expressly understood that the buyers sole and exclusive remedy shall be the replacement of defective products, and under no circumstances, shall **Stucco Supply** be liable for incidental or consequential damages. **Stucco Supply** neither assumes nor authorizes, any other to assume for it liability with respect to furnishing of the product.

**SAN JOSE STUCCO SUPPLY & DRYWALL - FROM START ↔ TO FINISH**

1601 LITTLE ORCHARD STREET, STE. E SAN JOSE, CA 95110

[WWW.STUCCOSUPPLYCO.COM](http://WWW.STUCCOSUPPLYCO.COM)