

SUPERIOR STUCCO DECK MUD

DESCRIPTION:

SUPERIOR STUCCO DECK MUD is a premium blend of Portland Cement and washed ocean sands. It has been pre-blended at our facility to ensure quality and consistency for the Tile Industry. **SUPERIOR STUCCO DECK MUD** is a tile mortar that is used as a Setting/Leveling bed on floors and countertops prior to setting tiles.

COVERAGE:

Approximately 6.5 sq. feet @ 1" thick.

MIXING:

SUPERIOR STUCCO DECK MUD only needs the addition of clean potable water to achieve the desired consistency. Mix with approximately 3-3-1/2 quarts of water for every 50lb bag, to desired consistency (typically a stiffer mix – mortar should ball up when compacted in your hand) Caution: Excessive water will reduce bond and workability.

Mixing with Admix: For improved performance use **SUPERIOR STUCCO ACRYLIC BONDER** in your mixing solution. 50% water:50% Acrylic Bonder- and up to 100% **SUPERIOR STUCCO ACRYLIC BONDER**.

CURING:

A minimum of 24 hours is required for curing. Consult Local Building Codes. May set tiles with Thin Set Mortar after curing period. In some cases you may set tile directly into wet pack.

SURFACE PREPARATION:

To ensure that **SUPERIOR STUCCO DECK MUD** bonds correctly, make sure the receiving surface is free of any contaminates, dust, debris, curing or cleaning agents, efflorescence, oils, etc.

LIMITATIONS:

Do not apply **SUPERIOR STUCCO DECK MUD** when ambient temperature is below 40 degrees F or above 100 degrees F. The temperature must stay consistent within this range for a minimum of 48 hours after application for material to cure properly. Do not add more water than what is prescribed when mixing, floating or troweling this product. Excessive or insufficient amounts of water can cause product failure. Do not deviate from mixing procedures or overmix, as this may cause product failure. **SUPERIOR STUCCO DECK MUD** is not intended to be left unfinished.

CLEAN UP:

Clean tools and surfaces immediately with water.

GUARANTEE

The above statement, recommendation, suggestions and technical data are based on the best knowledge to **Stucco Supply** and is given as information only, without any responsibility for their use. **Stucco Supply** makes no warranties or guarantees to this product, either expressed or implied with respect to merchantability or fitness for particular use of said product. Handling and use of product are out of the control of **Stucco Supply**, so no warranty is given.

SAN JOSE STUCCO SUPPLY & DRYWALL - FROM START ↔ TO FINISH

1601 LITTLE ORCHARD STREET, STE. E SAN JOSE, CA 95110

WWW.STUCCOSUPPLYCO.COM