

SUPERIOR STUCCO MULTI-BOND

DESIGNED TO ENHANCE GREATER BONDING

APPLICATION:

Take care that all Exterior or Interior surfaces are free of dirt, dust, oil, efflorescence and foreign matter. **Stucco Supply's SUPERIOR STUCCO MULTI-BOND** can be used with masonry, block, brick, clay, tile, plaster or cement products, etc. The light green color assures proper coverage of the surfaces. Apply with a brush, roller or sprayer. Wait until tacky and then apply cementitious material. **SUPERIOR STUCCO MULTI-BOND** gives the flexibility to apply finish even after drying with its re-emulsifying abilities. *Only re-emulsifies once, (1) time, within (10) days after application. Use without reducing or diluting.

COVERAGE:

The coverage of **SUPERIOR STUCCO MULTI-BOND** will vary due to job conditions, method of application and weather conditions. Typically (1) Gallon of **SUPERIOR STUCCO MULTI-BOND** will cover approximately 200-300 sq. feet. (5 Gallons: 1,000-1,500 sq. ft) Yields will vary depending on the substrate. **Stucco Supply** does not recommend diluting.

PATCHING:

SUPERIOR STUCCO MULTI-BOND may be used as a patching cement. Mix (1) part **SUPERIOR STUCCO MULTI-BOND** to (1) part Water, (3) parts Sand and (2) parts Cement. Mix into a paste. Depending on weather conditions and temperature, pot life of material should be between (2 - 6) hours.

SUPERIOR STUCCO MULTI-BOND meets or exceeds ASTM C-932-06 (Bonding Specs for exterior plaster), C-1059-99 (Bonding fresh concrete to existing concrete), C-1042-99 (Bond strength slant shear test) and C-631-95A (Bonding specs for Gypsum Plastering)

STORAGE:

SUPERIOR STUCCO MULTI-BOND should be stored in a cool, dry place out of direct sunlight. Keep above 40 degrees F and below 110 degrees F.

CLEAN UP:

Clean up with water immediately. **DO NOT ALLOW TO DRY BEFORE CLEAN UP.**

LIMITATIONS:

Do not apply **SUPERIOR STUCCO MULTI-BOND** when the temperature is below 40 degrees F or above 100 degrees F. This range of temperature must be kept for 48 hours to ensure proper curing. Keep away from hydrostatic pressure (Moisture/water) after applying and do not saturate surface with water prior to applying **SUPERIOR STUCCO MULTI-BOND**. Do not apply **SUPERIOR STUCCO MULTI-BOND** until surface is free of all contaminants. Protect the applied film from dirt and debris until the fresh product overlay is in place.

GUARANTEE

The above statement, recommendation, suggestions and technical data are based on the best knowledge to **Stucco Supply**. and as given as information only, without any responsibility for their use. **Stucco Supply** makes no warranties or guarantees to this product, either expressed or implied with respect to merchantability or fitness for particular use of said product. Handling and use of product are out of the control of **Stucco Supply**, so no warranty is given.

SAN JOSE STUCCO SUPPLY & DRYWALL - FROM START ↔ TO FINISH

1601 LITTLE ORCHARD STREET, STE. E SAN JOSE, CA 95110
WWW.STUCCOSUPPLYCO.COM